



# MATERIAL SAFETY DATA SHEET

## SECTION 1 — PRODUCT IDENTIFICATION

**Product identifier:** AlbaChem® Clear Screen

**Product Number:** 1641

**Preparation Date:** August 8, 2002

**Revision Date:** August 22, 2006

**D.O.T. Proper Shipping Name:** ORM-D Consumer Commodity

**NFPA Codes:** Health - 2, Flammability - 4, Corrosive - 0, Reactivity - 0

**Manufacturer's name and address:** Refer to supplier

**Supplier name and address:**

### ***ALBATROSS USA INC./EXPERT WORLDWIDE***

36-41 36<sup>th</sup> Street  
Long Island City, New York  
United States  
11106  
718-392-6272

5439 San Fernando Road West  
Los Angeles, California  
United States  
90039  
818-543-5850

**Emergency Telephone #:** Chemtrec (Day or Night) 800-424-9300

(For Chemical Emergency: Spill, Leak, Fire, Exposure or Accident)

This Material Safety Data Sheet contains environmental, health and toxicology information for your employees. Please make sure this information is given to them. It also contains information to help you meet community Right To Know emergency response reporting requirements under SARA TITLE III and many other laws. If you resell this product, this MSDS must be given to the buyer or the information incorporated in your MSDS.

This MSDS complies with 29 CFR 1910.1200 (The Hazard Communication Standard)

## SECTION 2 — COMPONENTS

Aromatic Petroleum Distillates  
CAS #: 64742-95-6

PEL: 150 ppm  
TLV: 100 ppm

Hydrocarbon Propellant  
CAS #: 68476-86-8

PEL: 800 ppm  
TLV: 800 ppm

Cyclohexanone  
CAS #: 108-94-1

\* PEL: 25 ppm - Skin  
TLV: 25 ppm - Skin

“\*” If present, IARL, NTP and OSHA carcinogens and chemical subject to this reporting requirements of SARA TITLE III, SECTION 313 are identified in this section.

## SECTION 3 — PHYSICAL DATA

**Specific Gravity:** 0.892

**V.O.C. (Grams per Liter):** 891.45

**Water Solubility:** Not Soluble

**Appearance:** Clear Solvent

**Boiling Point for Product:** 308 Degree F.

**Vapor Pressure for Product:** 2.0 mm Hg

**Vapor Density for Product (Air = 1):** >1.00

**SECTION 4 — FIRE AND EXPLOSION DATA****Flash Point (COC):** Level 3 Aerosol**Explosive Limit (Product):** Lower -  
SEC04.45

Upper -

**Fire and Explosion Hazards:**

This product releases Flammable Vapors at well below ambient temperatures and readily forms flammable mixtures with air exposed to an ignition source. It will burn in the open or be explosive in confined spaces. Its vapors are heavier than air and may travel long distances to a point of ignition, and then flash back. Alkane/Chlorine gas mixtures have produced explosions.

**Extinguishing Media:**

Dry Chemical. CO2. Halogenated Extinguishing Agent. Stop Gas Flow.

**Special Fire Fighting Procedures:**

Gas fires should not be extinguished unless the gas flow can be stopped immediately. Allow the fire to burn itself out. If the source cannot be shut off immediately, all equipment and surfaces exposed to the fire should be cooled with water to prevent over-heating, flash-backs, or explosions. Control fire until gas supply can be shut off. Use proper protective equipment. Use fresh air respirator when exposure to hazardous concentrations of toxic gases is possible.

**Fire Fighting:**

Use water spray to cool fire exposed surfaces and to protect personnel. Isolate “fuel” supply from fire. Use foam, dry chemical, or water spray to extinguish fire. Avoid spraying water directly into storage containers due to danger of boil over. This liquid is volatile and gives off invisible vapors. Either the liquid or vapour may settle in low areas or travel some distance along the ground or surface to ignition sources where they may ignite or explode.

**SECTION 5 — HEALTH HAZARD DATA**

SEC05.20

**General:**

This material is an aspiration hazard and defats the skin. Breathing vapors of high concentrations may cause CNS depression.

**Eye Contact:**

Slightly irritating but does not injure eye tissue.

**Skin Contact:**

Low order of toxicity. Frequent or prolonged contact may irritate and cause dermatitis. Skin contact may aggravate an existing dermatitis condition.

**Inhalation:**

High vapour/aerosol concentrations (greater than approximately 100 ppm) are irritating to the eyes and the respiratory tract, may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death.

**Ingestion:**

Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possible minimal toxicity.

**FIRST AID****Eye Contact:**

Flush eyes with large amounts of water until irritation subsides. If irritation persists, get medical attention.

**Skin Contact:**

Flush with large amounts of water; use soap if available. Remove grossly contaminated clothing, including shoes, and leather before reuse.

**Inhalation:**

Using proper respiratory protection, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. All for prompt medical attention.

**Ingestion:**

If swallowed, DO NOT induce vomiting. Keep at rest. Get prompt medical attention.

### PRECAUTIONS

**Special Precautions:**

Health studies have shown that many hydrocarbons pose potential human health risks which may vary from person to person. As a precaution, exposure to liquids, vapors, mists or fumes should be minimized.

**Personal Protection:**

For open systems where contact is likely, wear safety glasses with side shields, long sleeves, and chemical resistant gloves. Where concentrations in air may exceed the limits, work practice or other means of exposure reduction are not adequate, NIOSH/MSHA approved respirators may be necessary to prevent overexposure by inhalation.

**Ventilation:**

The use of mechanical dilution ventilation is recommended whenever this product is used in a confined space, is heated above ambient temperatures, or is agitated.

(PROPOSITION 65): SEC05

WARNING: IN ACCORDANCE WITH PROP 65, THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS AND OTHER REPRODUCTIVE HARM.

## SECTION 6 — REACTIVITY DATA

SEC06.20

**Stability:** Stable.

**Conditions to Avoid:** Not Applicable.

**Hazardous Polymerization:** Will not occur.

**Materials and Conditions to Avoid Incompatibility:** Strong oxidizing agents.

**Hazardous Decomposition Products:** None

## SECTION 7 — SPILL OR LEAK PROCEDURES

SEC07.45

**Steps to be Taken in Case Container is Punctured and Material is Released:**

Clean up area by mopping or with absorbent materials and place in closed container for disposal. Consult Federal, State, and local disposal authorities.

**Waste Disposal Method:**

Consult local authorities for proper waste disposal procedures. Empty de-pressurized containers can not be reused. Can which are pressurized or contain liquid must be disposed of in a permitted waste management facility. Consult Federal, State, and local disposal authorities for approved procedures.

## SECTION 8 — PROTECTIVE EQUIPMENT TO BE USED

SEC08.20

**Ventilation Requirement:**

Use adequate level exhaust ventilation. Note: where carbon monoxide may be generated, special ventilation may be required. Local exhaust recommended when appropriate to control employee exposure.

**Respiratory Protection:**

Based on contamination level and working limits of the respirator, use a respirator approved by NIOSH/MSHA.

**Eyes:**

Face shield and goggles or chemical goggles should be worn.

**Gloves:**

Impervious gloves should be worn. Gloves contaminated with the product should be discarded. Polyfluorinated polyethylene has been suggested.

**Other Clothing Equipment:**

Standard work clothing. Standard work shoes; discard if shoes cannot be decontaminated. Store contaminated clothing in well ventilated cabinets or closed containers. Wash contaminated clothing and dry before reuse.

**Respiratory Protection:**

In situations where vapor concentrations exceed the recommended exposure limits, a NIOSH approved organic vapor cartridge or air-supplying respirator should be worn.

## SECTION 9 — SPECIAL PRECAUTIONS OR OTHER COMMENTS

SEC09.45

**Handling Storage and Decontamination Procedures:**

When utilizing pressurized containers follow standard safety practices for handling aerosols.

**General Comments:**

Do not store at temperature above 120 degree F. Odor is not an adequate warning of potentially hazardous concentrations in air. Releases of these gases may cause a flammable atmosphere with explosion potential.

**Precautionary Statement:**

Please read and follow the directions on the product label. They are your best guide to using this product in the most effective way, and give the necessary safety precautions to protect your health.

---

---

### ADDITIONAL COMMENTS:

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modification of the information, we do not assume any responsibility for the results of its use. This information is furnished upon conditions that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.