



MATERIAL SAFETY DATA SHEET

SECTION 1 — PRODUCT NAME & HAZARD SUMMARY

Product identifier: Formula L.R. (Lipstick Remover)

Product Number: 1037

Product Use: Oily Gel Type Paint & Grease Remover

Primary Use: Spot Removal

Preparation Date: June 2000

Revision Date: February 2008

Manufacturer's name and address: Refer to supplier

Supplier name and address:

ALBATROSS USA INC./EXPERT WORLDWIDE

36-41 36th Street
Long Island City, New York
United States
11106
718-392-6272

5439 San Fernando Road West
Los Angeles, California
United States
90039
818-543-5850

Emergency Telephone #: Chemtrec (Day or Night) 800-424-9300 (For Chemical Emergency: Spill, Leak, Fire, Exposure or Accident)

IMPORTANT: Read this MSDS before handling and disposing of this product. Pass this information on to employees, customers, and users of this product.

NFPA

HAZARD

Health

Fire

Reactivity

RATING

2 Moderate

2 Moderate

0 Minimal

SARA TITLE III

SECTION 313

Applicable()

Not Applicable (X)

VOC Content: 785 grams per liter

CANADA (WHMIS)

B: Flammable, Combustible

D2: Causing other Toxic Effects

SECTION 2 — HAZARDOUS COMPONENTS

	%	OSHA(ppm) PEL	ACGIH(ppm) TWA	LD ₅₀ (mg/kg) STEL	
Aromatic Hydrocarbon C.A.S. #4742-94-5	46.0	N.AV.	10	15	N.AV.
Aliphatic Hydrocarbon C.A.S. #64742-88-7	27.0	500	100	N.AV.	N.AV.

Ingredients Not Identified Are Non-Hazardous.

SECTION 3 — PHYSICAL & CHEMICAL DATA

Appearance: Clear to Opaque Gel

Odor: Petroleum

Boiling Point: >355° F (179° C)

Freezing Point: N.AV.

pH: N.A.P.

Evaporation Rate (H₂O = 1): 1.0

Vapor Density (Air = 1): N.AV.

Vapor Pressure (MM): N.AV.

Solubility in Water: Appreciable

Specific Gravity (Water = 1): 0.84

% Volatile: 65%

Co-Efficient of Water/Oil Distribution: N.AV.

Odor Threshold (ppm): N.AV.

SECTION 4 — FIRE & EXPLOSION HAZARDS**Flash Point:** >142° F (61° C)**Flammable Limits in Air, % By Volume:** N.AV.**Fire Fighting Media (1990 Emergency Response Guidebook, DOT P 5800.5):** Dry chemical, CO₂, water spray or alcohol foam.**Special Fire Fighting Procedures:** Wear self contained breathing apparatus.**Unusual Fire and Explosion Hazard:** None**Hazardous Combustion Products:** Oxides of Carbon**Conditions of Flammability:** High heat and sources of ignition**Auto Ignition Temp. (° C):** N.AV.**Explosion Data: - Sensitivity to Mechanical Impact:** N.AP.**Sensitivity to Static Discharge:** N.AV.**SECTION 5 — REACTIVITY HAZARD DATA****Stability (Conditions to Avoid):** Stable**Incompatibility (Materials to Avoid):** Strong oxidizing agents**Hazardous Decomposition Products:** Thermal decomposition may release Oxides of Carbon**Hazardous Polymerization (Conditions to Avoid):** Will no occur**SECTION 6 — HEALTH HAZARD DATA****Primary Route(s) of Entry:** Inhalation _____ Skin X Ingestion _____**Warning!** May Cause Eye and Skin Irritation. May Be Harmful if Swallowed.**Signs & Symptoms of Exposure: (Acute & Chronic)****EYES:** May cause irritation, corneal damage and conjunctivitis.**SKIN:** May cause irritation and defatting of skin. May cause dermatitis. Butyl Cellosolve may be absorbed through skin to cause headache, drowsiness, tremors and blurred vision. May affect blood chemistry, kidneys and liver. Prolonged contact may induce pathological lesions of the brain, lungs, liver, meninges and heart.**INGESTION:** May produce narcotic responses, central nervous system depression with giddiness, headache, dizziness, nausea and vomiting. May cause diarrhea and gastrointestinal irritation. May affect blood chemistry, kidneys and liver. May produce pathological lesions of the brain, lungs, liver, meninges and heart.**INHALATION:** Low hazard unless heated or misted.**IRRITANCY OF PRODUCT:** N.AV.**SENSITIZATION TO PRODUCT:** N.AV.**CARCINOGENICITY, REPRODUCTIVE TOXICITY, TERATOGENICITY, MUTAGENICITY:** N.AV.**TOXICOLOGICALLY SYNERGISTIC PRODUCTS:** N.AV.**Emergency & First Aid Procedures:****EYES:** Remove contact lenses, if worn. Flush with water for at least 15 minutes. Call a physician.**SKIN:** Remove contaminated clothing, wash affected area with soap and water. If any symptoms of contact appear, get medical help.**INHALATION:** Remove to fresh air. If breathing has stopped, perform artificial respiration. Get medical help.**INGESTION:** Do NOT induce vomiting, get medical help. If vomiting occurs, keep head below hips to prevent

SECTION 7 — SPILL AND LEAK PROCEDURES

Large Spills: Contain and transfer to drums for use or disposal.

Small Spills: Absorb onto rags. Clean rags in cleaning unit.

Waste Disposal Method: May be considered a hazardous waste, dispose of according to all applicable regulations. Incineration in permitted facilities or disposal in permitted land fill are preferred disposal methods.

Handling Procedures & Equipment: Avoid direct contact.

Storage Requirements: Store away from heat, flames and other sources of ignition.

SECTION 8 — SPECIAL PROTECTION, PREVENTATIVE MEASURES/IN CASE OF LARGE SPILL OR FIRE

Engineering Controls/Ventilation: Local exhaust system sufficient to maintain exposure below TWA values.

Respirator: The following respirators are recommended & ranked in order from minimum to maximum protection:

Chemical Cartridge Respirator with an Organic Vapor Cartridge with a Full Face Piece.

Gas Mask with Organic Vapor Canister with a Full Face Piece.

Type "C" Supplied-Air Respirator with Full Face Piece.

Self-Contained Breathing Apparatus with a Full Face Piece Operated in Pressure-Demand.

Personal Protective Equipment: Water goggles and nitrile rubber gloves when handling product.

SECTION 9 — TRANSPORTATION DATA

DOT Hazard Classification 49 CFR172.101: Combustible liquid, not regulated.

DOT Label: None

U.N./IATA: Not regulated

SECTION 10 — STATE RIGHT TO KNOW INFORMATION

Aromatic Hydrocarbon - C.A.S. #4742-94-5, **Aliphatic Hydrocarbon** - C.A.S. #64742-88-7, **Glycol Ether** - C.A.S. #34590-94-8, **Sorbitan Monooleate** – C.A.S. #1338-43-8, **Phosphate Ester** – C.A.S. #68954-84-7

Abbreviations:

N/Ap – Not Applicable

OSHA – Occupational Safety and Health Act

C.A.S. – Chemicals Abstract Service Number

PEL – Permissible Exposure Limit

SARA Title III, Sec. 313 – Superfund Amendments & Reauthorization Act

ACGIH – American Conference of Governmental Industrial Hygienists

N/Av – Not Available

N.Ap -- Not Applicable

U.N. -- United Nations

DOT – United States Department of Transportation

WHMIS – Workplace Hazardous Material Information System
TWA – Time Weighted Average for 8 Hours
Mg/M³ – Milligrams per Cubic Meter of Air
NFPA -- National Fire Protection Agency
(C) -- Ceiling, Limit for Exposure
Mg/Kg -- Milligrams per Kilogram (1,000 grams)
R.Q. -- Amount of spill that must be reported to EPA
LD50 -- Lethal Dose for 50% Test Animals
STEL -- Short Term Exposure Level (15 min)
ppm -- part(s) per million
SKN -- Skin Effects
IATA -- International Air Transport Association

We cannot anticipate all conditions under which this information and our products, or the products of other manufacturers in combination with our products, may be used. We accept no responsibility for results obtained by the application of this information or the safety and suitability of our products, either alone or in combination with other products. We sell the products without warranty, and buyers and users assume all responsibility and liability for loss or damage arising from the handling and use of our products, whether alone or in combination with other products.